



Specifications

Reikken Model	Nominal Voltage	Continuous Wattage	Weight lbs	Capacity Ah	Group Size	Positive Term
JB609	12	650	12	18	-	R
HO709	12	750	13	20	-	R
JB809	12	850	21	35	U-1	L
JB1209	12	1200	28	50	-	R
JB1409	12	1400	34	55	22/51	L
JB1809	12	1800	48	75	24	L
JB2009	12	2000	57	90	27	L
JB2409	12	2400	66	110	31	L
HO3209	12	3200	70	120	31	L
JB-Reikken	12	5200	123	200	-	R
JB34UH	12	na	42	70	34	L

Reikken Model	Power Cell Dimensions					
	Inches			Millimeters		
	L	W	H	L	W	H
JB609	7.13	3.00	6.54	181	76	165
HO709	7.13	3.03	6.57	181	77	166
JB809	7.75	5.11	6.25	197	130	159
JB1209	7.76	6.54	6.86	197	166	174
JB1409	9.02	5.43	8.27	229	138	210
JB1809	10.24	6.66	8.31	260	169	211
JB2009	12.10	6.66	8.31	307	169	211
JB2409	13.04	6.82	8.39	331	173	213
HO3209	13.00	6.73	8.66	330	171	220
JB-Reikken	20.57	9.46	8.51	522	240	216
JB34UH	10.24	6.61	7.20	260	168	183

Specifications are subject to change without notice. Reikken makes no representation or warranty whatsoever regarding the completeness, accuracy, up to date state, or adequacy of, or the suitability, functionality, availability, or operation of the information or materials it contains and the eventuality(s), probability(s) and possibility (s) might prevail whereby information featured onto The web site or printed materials may contain technical inaccuracies, grammatical errors, typographical errors, source-data errors, misprints or omissions, out of date information, technical or quote inaccuracies.